



SAFETY DATA SHEET

Quik-Shield 155 2.8 W Resin (B)

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code: QS 155 2.8 W B
Product Name: Quik-Shield 155 2.8 W Resin (B)
Company Name: SWD URETHANE
 539 S. Drew St.
 Mesa, AZ 85210,
Web site address: www.swdurethane.com
Emergency Contact: CHEMTREC
 (800) 424-9300

2. HAZARDS IDENTIFICATION

Acute Toxicity: Oral, Category 4
Acute Toxicity: Skin, Category 5
Serious Eye Damage/Eye Irritation, Category 2B



GHS Signal Word: **Warning**

GHS Hazard Phrases: H302 - Harmful if swallowed.
 H313 - May be harmful in contact with skin.
 H320 - Causes eye irritation.

GHS Precautionary Phrases: P264 - Wash hands thoroughly after handling.
 P270 - Do not eat, drink or smoke when using this product.
 P273 - Avoid release to the environment.

GHS Response Phrases:

GHS Storage and Disposal Phrases:

Other Hazards: Causes mild skin irritation. Harmful to aquatic life.

Inhalation: May be harmful if inhaled. Causes respiratory tract irritation. May cause narcotic effects in high concentration. Eye irritation, vertigo, and nausea were reported in humans exposed at 2200 ppm.

Skin Contact: May be harmful if absorbed through the skin. Causes skin irritation. Causes moderate skin irritation. May cause dermatitis.

Eye Contact: Causes eye irritation.

Ingestion: Harmful if swallowed. May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May cause central nervous system depression.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Ingredients/Components	Concentration
77098-07-8	1,2-Benzenedicarboxylic acid, 3,4,5,6-tetrabromo-, mixed esters with diethylene glycol and propylen	< 3.0 %
NA	Halogenated Phosphate	7.0 -13.0 %
NA	Proprietary Blowing Agent	1.0 -3.0 %
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	< 4.0 %



4. FIRST AID MEASURES

Emergency and First Aid Procedures:

In Case of Inhalation: If breathed in, move person into fresh air. If inhaled, remove to fresh air. If not breathing, give artificial respiration. Get medical aid.

In Case of Skin Contact: Wash off with soap and plenty of water. Consult a physician. In case of contact, flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical aid if irritation develops and persists. Wash clothing before reuse.

In Case of Eye Contact: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical aid.

In Case of Ingestion: Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician. Get medical aid.

Signs and Symptoms Of Exposure: To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Note to Physician: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Flash Pt:

Explosive Limits: LEL: UEL:

Autoignition Pt:

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.

Fire Fighting Instructions: Wear self contained breathing apparatus for fire fighting if necessary. As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Vapors may form explosive mixtures with air. Use water spray to keep fire-exposed containers cool. Flammable liquid and vapor. Fire or excessive heat may result in violent rupture of the container due to bulk polymerization. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas.

Flammable Properties and Hazards:

Hazardous Combustion

Products:

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Personal precautions.
Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation.

Environmental precautions.
Do not let product enter drains.

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal. Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Remove all sources of ignition. Use a spark-proof tool.



SAFETY DATA SHEET

Quik-Shield 155 2.8 W Resin (B)

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:	Avoid inhalation of vapor or mist. Normal measures for preventive fire protection. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid contact with eyes, skin, and clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Avoid ingestion and inhalation. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Use only with adequate ventilation. Pure vapor will be uninhibited and may polymerize in vents or other confined spaces.
Precautions To Be Taken in Storing:	Keep container tightly closed in a dry and well-ventilated place. Keep away from sources of ignition. Store in a tightly closed container. Flammables-area. Store protected from light and air.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
77098-07-8	1,2-Benzenedicarboxylic acid, 3,4,5,6-tetrabromo-, mixed esters with diethylene glycol and propylen			
NA	Halogenated Phosphate			
NA	Proprietary Blowing Agent		TLV: 200 ppm	
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	PEL: 50 ppm	TLV: 20 ppm	

Respiratory Equipment (Specify Type): Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Eye Protection: Face shield and safety glasses. Wear chemical splash goggles.

Protective Gloves: Handle with gloves. Wear appropriate protective gloves to prevent skin exposure.

Other Protective Clothing: Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.): Use process enclosure, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Work/Hygienic/Maintenance Practices: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.



SAFETY DATA SHEET

Quik-Shield 155 2.8 W Resin (B)

Page: 4 of 7

Printed: 03/27/2020

Revision: 03/27/2020

Supersedes Revision: 02/03/2014

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Viscous.
Light. Brown.

pH:

Melting Point:

Boiling Point:

Flash Pt:

Evaporation Rate:

Flammability (solid, gas):

Explosive Limits: LEL: UEL:

Vapor Pressure (vs. Air or mm Hg):

Vapor Density (vs. Air = 1):

Specific Gravity (Water = 1):

Solubility in Water:

Octanol/Water Partition

Coefficient:

Autoignition Pt:

Decomposition Temperature:

Viscosity:

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]

Conditions To Avoid - No data available.

Instability: Light, ignition sources, Exposure to air.

Incompatibility - Materials To Avoid: No dangerous reaction known under conditions of normal use. Strong bases, Copper.

Hazardous Decomposition or Byproducts: formed under fire conditions. Carbon oxides, Phosphorous oxides, Hydrogen chloride gas, Thermal decomposition 244 °C Hydrogen chloride, phosgene, Carbon monoxide.

Possibility of Hazardous Reactions: Will occur [] Will not occur [X]

Conditions To Avoid -

Hazardous Reactions:



SAFETY DATA SHEET

Quik-Shield 155 2.8 W Resin (B)

11. TOXICOLOGICAL INFORMATION

Toxicological Information:	<p>Epidemiology: No data available. Teratogenicity: No data available. Reproductive Effects: Mutagenicity: Neurotoxicity: Other Studies: CAS# NA: Skin corrosion/irritation, Skin sensitization, This product does not contain any relevant quantities of materials with critical values that have to be monitored in the workplace., Rabbit, 0.000 , Mild. Results: Sense Organs and Special Senses (Nose, Eye, Ear, and Taste):Eye:Lacrimation. Behavioral: Tremor. Lungs, Thorax, or Respiration:Cyanosis.</p>
Irritation or Corrosion:	<p>Skin - rabbit - Mild skin irritation - 24 h. Serious eye damage/eye irritation: Eyes - rabbit - Mild eye irritation.</p>
Carcinogenicity/Other Information:	<p>Carcinogenicity. IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH. NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. CAS# 156-60-5: Not listed by ACGIH, IARC, NTP, or CA Prop 65.</p>

CAS #	Ingredients/Components	NTP	IARC	ACGIH	OSHA
77098-07-8	1,2-Benzenedicarboxylic acid, 3,4,5,6-tetrabromo-, mixed esters with diethylene glycol and propylen				
NA	Halogenated Phosphate				
NA	Proprietary Blowing Agent				
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}		3	A3	

12. ECOLOGICAL INFORMATION

Persistence and Degradability:	No data available.
Bioaccumulative Potential:	No data available.
Mobility in Soil:	No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method:	<p>Product. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.</p> <p>Contaminated packaging. Dispose of as unused product. Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. RCRA P-Series: None listed. RCRA U-Series: CAS# 156-60-5: waste number U079.</p>
-------------------------------	---



SAFETY DATA SHEET

Quik-Shield 155 2.8 W Resin (B)

14. TRANSPORT INFORMATION

GHS Classification:

- Acute Toxicity: Oral, Category 4 - Warning! Harmful if swallowed
- Acute Toxicity: Skin, Category 5 - Warning! May be harmful in contact with skin
- Skin Corrosion/Irritation, Category 3 - Warning! Causes mild skin irritation
- Serious Eye Damage/Eye Irritation, Category 2B - Warning! Causes eye irritation
- Aquatic Toxicity (Acute), Category 3 - Harmful to aquatic life

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not Regulated.
DOT Hazard Class:
UN/NA Number:

LAND TRANSPORT (Canadian TDG):

TDG Shipping Name: Not Regulated.
UN Number:
Hazard Class: **TDG Classification:**

MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Not Regulated.
UN Number: **Packing Group:**
Hazard Class:

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Not Regulated.
UN Number: **Packing Group:**
Hazard Class:

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Ingredients/Components	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
77098-07-8	1,2-Benzenedicarboxylic acid, 3,4,5,6-tetrabromo-, mixed esters with diethylene glycol and propylen	No	No	No
NA	Halogenated Phosphate	No	No	No
NA	Proprietary Blowing Agent	No	No	No
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	No	No	Yes-Cat. N230

CAS # Ingredients/Components

Other US EPA or State Lists

77098-07-8	1,2-Benzenedicarboxylic acid, 3,4,5,6-tetrabromo-, mixed esters with diethylene glycol and propylen	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
NA	Halogenated Phosphate	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 8D TERM; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
NA	Proprietary Blowing Agent	CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC: Cat. IIa,



SAFETY DATA SHEET

Quik-Shield 155 2.8 W Resin (B)

Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Yes - Cat.; NC TAP: Yes - Cat.; NJ EHS: Yes - Cat.; NY Part 597: No; PA HSL: Yes - 1; SC TAP: Yes - Cat.; WI Air: Yes

CAS #	Ingredients/Components	International Regulatory Lists
--------------	-------------------------------	---------------------------------------

77098-07-8	1,2-Benzenedicarboxylic acid, 3,4,5,6-tetrabromo-, mixed esters with diethylene glycol and propylen	Canadian DSL: Yes; Canadian NDSL: No
------------	---	--------------------------------------

NA	Halogenated Phosphate	Canadian DSL: Yes; Canadian NDSL: No
----	-----------------------	--------------------------------------

NA	Proprietary Blowing Agent	Canadian DSL: No; Canadian NDSL: No
----	---------------------------	-------------------------------------

111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	Canadian DSL: Yes; Canadian NDSL: No
----------	--	--------------------------------------

Regulatory Information:

This product contains no chemicals subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 40 CFR part 372.

Regulatory Information Statement:

16. OTHER INFORMATION

Revision Date: 03/27/2020

Additional Information About This Product:

Company Policy or Disclaimer:

While the information and recommendations in this publication are given to the best of our knowledge, and information at the date of publication, nothing herein is to be construed as a warranty, expressed or otherwise. In all cases, it is the responsibility of the user to determine the applicability of such information, and recommendations or the suitability of any product for its own particular purpose.

The product may present hazards and should be used with caution. While certain hazards are described in this Safety Data Sheet, no guarantee is made that these are the only hazards that exist. Hazards, toxicity and behavior of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behavior should be determined by the user and made known to handlers, processors and end users.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED SWD EMPLOYEE SHALL PROVIDE, OR MAKE AVAILABLE, DATA SHEETS FOR SWD PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT THE WRITTEN PERMISSION OF SWD. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET OR QUESTIONS REGARDING THIS DATA SHEET SHOULD BE DIRECTED TO SWD AT 800-828-1394.